

Velocity Harness

Part #	Size	Description
01700	S - L	Velocity HUV w/ Chest & Leg Pass-Through Buckles
01701	XL - 2XL	Velocity HUV w/ Chest & Leg Pass-Through Buckles
01702	S - L	Velocity w/ 3 D-rings, and Chest & Leg Pass-Through Buckles
01703	S - L	Velocity HUV w/ Chest Pass-Through Buckle and Leg Tongue Buckles
01704	XL - 2XL	Velocity HUV w/ Chest Pass-Through Buckle and Leg Tongue Buckles
01705	S - L	Velocity w/ 3 D-rings, Chest Pass-Through Buckle, and Leg Tongue Buckles
01706	XL - 2XL	Velocity w/ 3 D-rings, Chest Pass-Through Buckle, and Leg Tongue Buckles
01740	S - L	Velocity Stretch w/Pass-Through Chest & Leg Buckles

Compliant with all applicable OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Product-Specific Applications



Personal Fall Arrest: A Velocity Harness may be used in Personal Fall Arrest applications as a component of a Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', unless used in combination with equipment explicitly certified for extended free fall. Applicable D-ring: Dorsal.



Restraint: A Velocity Harness may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



Work Positioning: A Velocity Harness, configured with side or shoulder D-rings, may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side, Shoulder.



Rescue/Confined Space: A Velocity Harness may be used in Rescue/Confined Space applications. Rescue systems function to safely recover a worker from a confined location or after exposed to a fall. There are various configurations of Rescue systems depending on the type of rescue. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. No free fall is permitted. Applicable D-rings: Dorsal, chest, shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs. if used in combination with equipment explicitly certified for such use.

Materials: polyester and nylon.

Red internal webbing contrasts with yellow external webbing, which allows for easy determination of damage or exposure to forces of fall arrest during equipment inspection.

Always follow all manufacturer's instructions for proper adornment and use. Some steps of adorning a harness may require assistance from another person.

Upon completely adorning a harness, Guardian Fall Protection recommends that another person, with knowledge of the safe and correct use of the harness, inspect to ensure the harness is being worn correctly.

Many models now featuring our Comfi-Fit Pad and Sub-Pelvic Stitching! Contact customer service for details.



#01740